

Appl. No. 10/708,047
Amdt. dated July 12, 2006
Reply to Office action of April 24, 2006

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

5 **Listing of Claims:**

1. (Previously Presented) A light-emitting device with compound substrate comprising:

10 a compound substrate comprising a high thermal conductive layer and
a substrate disposed around the high thermal conductive layer;
a transparent adhesive layer formed on the compound substrate; and
a light-emitting stack layer formed on the transparent adhesive layer.

2. (Cancelled)

15 3. (Previously Presented) The light-emitting device of claim 1 wherein the
transparent adhesive layer is a conductive transparent adhesive layer.

4. (Previously Presented) The light-emitting device of claim 1 wherein the
transparent adhesive layer is an insulating transparent adhesive layer.

20

5-7. (Cancelled)

8. (Previously Presented) The light-emitting device of claim 1 further
comprising a first reaction layer between the compound substrate and the
transparent adhesive layer.

25

9. (Previously Presented) The light-emitting device of claim 1 further

Appl. No. 10/708,047
Amdt. dated July 12, 2006
Reply to Office action of April 24, 2006

comprising a second reaction layer between the transparent adhesive layer and the light-emitting stack layer.

5 10. (Original) The light-emitting device of claim 8 further comprising a metal reflecting layer between the compound substrate and the first reaction layer.

10 11. (Original) The light-emitting device of claim 9 further comprising a metal reflecting layer between the second reaction layer and the light-emitting stack layer.

15 12. (Original) The light-emitting device of claim 11 further comprising a transparent conductive layer between the metal reflecting layer and the light-emitting stack layer.

13-14. (Cancelled)

20 15. (Original) The light-emitting device of claim 1 further comprising a connection layer between the high thermal conductive layer and the substrate.

25 16. (Previously Presented) The light-emitting device of claim 1 wherein the high thermal conductive layer comprises at least one material selected from a material group consisting of Cu, Al, Au, Ag, W, and alloys of these metals.

17. (Previously Presented) The light-emitting device of claim 15 wherein the connection layer comprises at least one material selected from a

Appl. No. 10/708,047
Amdt. dated July 12, 2006
Reply to Office action of April 24, 2006

material group consisting of indium tin oxide, GeAu, BeAu, Au, SiNx, SiO₂, Cu, Ti, and Pd.

18. (Cancelled)

5

19. (Previously Presented) The light-emitting device of claim 1 wherein the transparent adhesive layer comprises at least one material selected from a material group consisting of polyimide (PI), benzocyclobutane (BCB), and perfluorocyclobutene (PFCB).

10

20. (Previously Presented) The light-emitting device of claim 3 wherein the conductive transparent adhesive layer comprises at least one material selected from a material group consisting of intrinsically conducting polymer and polymer doped with a conductive material.

15

21. (Previously Presented) The light-emitting device of claim 20 wherein the conductive material comprises at least one material selected from a material group consisting of indium tin oxide, cadmium tin oxide, antimony tin oxide, zinc oxide, zinc tin oxide, Au, and Ni/Au.

20

22-24. (Cancelled)

25

25. (Previously Presented) The light-emitting device of claim 8 wherein the first reaction layer comprises at least one material selected from a material group consisting of SiNx, Ti, and Cr.

26. (Previously Presented) The light-emitting device of claim 9 wherein the second reaction layer comprises at least one material selected from a

Appl. No. 10/708,047
Amdt. dated July 12, 2006
Reply to Office action of April 24, 2006

material group consisting of SiNx, Ti, and Cr.

27. (Previously Presented) A light-emitting device with compound substrate comprising:

- 5 a compound substrate comprising a high thermal conductive layer and
 a substrate disposed around the high thermal conductive layer;
 an opaque adhesive layer formed on the compound substrate; and
 a light-emitting stack layer formed on the opaque adhesive layer.

- 10 28. (Previously Presented) The light-emitting device of claim 27 wherein
 the opaque adhesive layer is a conductive opaque adhesive layer.

29. (Previously Presented) The light-emitting device of claim 27 wherein
 the opaque adhesive layer is an insulating opaque adhesive layer.

15

30. (Previously Presented) The light-emitting device of claim 27 further
 comprising a first reaction layer between the compound substrate and the
 opaque adhesive layer.

- 20 31. (Previously Presented) The light-emitting device of claim 30 further
 comprising a second reaction layer between the opaque adhesive layer
 and the light-emitting stack layer.

25 32. (Previously Presented) The light-emitting device of claim 31 further
 comprising a metal reflecting layer between the second reaction layer
 and the light-emitting stack layer.

33. (Previously Presented) The light-emitting device of claim 32 further

Appl. No. 10/708,047
Amdt. dated July 12, 2006
Reply to Office action of April 24, 2006

comprising a transparent conductive layer between the metal reflecting layer and the light-emitting stack layer.

34. (Previously Presented) The light-emitting device of claim 27 further comprising a connection layer between the high thermal conductive layer and the substrate.

35. (Previously Presented) The light-emitting device of claim 27 wherein the high thermal conductive layer comprises at least one material selected from a material group consisting of Cu, Al, Au, Ag, W, and alloys of these metals.

36. (Previously Presented) The light-emitting device of claim 34 wherein the connection layer comprises at least one material selected from a material group consisting of indium tin oxide, GeAu, BeAu, Au, SiNx, SiO₂, Cu, Ti, and Pd.

37. (Previously Presented) The light-emitting device of claim 30 wherein the first reaction layer comprises at least one material selected from a material group consisting of SiNx, Ti, and Cr.

38. (Previously Presented) The light-emitting device of claim 31 wherein the second reaction layer comprises at least one material selected from a material group consisting of SiNx, Ti, and Cr.

39. (Currently Amended) A light-emitting device with compound substrate comprising:
a compound substrate comprising a high thermal conductive layer and

Appl. No. 10/708,047
Amdt. dated July 12, 2006
Reply to Office action of April 24, 2006

a substrate disposed around the high thermal conductive layer;
a metal ~~adhesive~~-layer formed on the compound substrate; and
a light-emitting stack layer formed on the metal ~~adhesive~~-layer[[]];
wherein the metal layer is formed to enhance adhesion between the
5 compound substrate and the light-emitting stack layer.

40. (Currently amended) The light-emitting device of claim 39 further
comprising a metal reflecting layer between the metal ~~adhesive~~-layer and
the light-emitting stack layer.

10 41. (Previously Presented) The light-emitting device of claim 40 further
comprising a transparent conductive layer between the metal reflecting
layer and the light-emitting stack layer.

15 42. (Previously Presented) The light-emitting device of claim 39 further
comprising a connection layer between the high thermal conductive layer
and the substrate.

20 43. (Previously Presented) The light-emitting device of claim 39 wherein
the high thermal conductive layer comprises at least one material
selected from a material group consisting of Cu, Al, Au, Ag, W, and
alloys of these metals.

25 44. (Previously Presented) The light-emitting device of claim 42 wherein
the connection layer comprises at least one material selected from a
material group consisting of indium tin oxide, GeAu, BeAu, Au, SiNx,
SiO₂, Cu, Ti, and Pd.

Appl. No. 10/708,047
Amdt. dated July 12, 2006
Reply to Office action of April 24, 2006

45. (Currently Amended) The light-emitting device of claim 39 wherein the metal ~~adhesive~~-layer comprises at least one material selected from a material group consisting of In, Sn, Al, ~~[[au]]Au~~, Pt, Zn, Ge, Ag, Ti, Pb, Pd, Cu, and alloys of these metals.

5

46. (Currently Amended) The light-emitting device of claim 39 wherein the metal ~~adhesive~~-layer is a metal reflecting ~~adhesive~~-layer.